

| Type description | Capacity in kg following FEM* | | | | | Lifting speed m/min | Chain mm |
|------------------|-------------------------------|-----------|----------|----------|----------|------------------------|-------------|
| | 1Bm M3 | 1Am M4 | 2m M5 | 3m M6 | 4m M7 | | |
| GCH 250/1N | 250 | 200 | 160 | 125 | 100 | 8 | 4x12.3 |
| GCH 250/1NF | 250 | 200 | 160 | 125 | 100 | 8/2 | 4x12.3 |
| GCH 250/1SF | 160 | 125 | 100 | 80 | 60 | 12.5/3 | 4x12.3 |
| GCH 250/1HF | 100 | 80 | 60 | 50 | 40 | 20/5 | 4x12.3 |
| GCH 250/2N | 500 | 400 | 320 | 250 | 200 | 4 | 4x12.3 |
| GCH 250/2NF | 500 | 400 | 320 | 250 | 200 | 4/1 | 4x12.3 |
| GCH 250/2SF | 320 | 250 | 200 | 160 | 125 | 6.3/1.5 | 4x12.3 |
| GCH 500/1N | 500 | 400 | 320 | 250 | 200 | 8 | 5x15.3 |
| GCH 500/1NF | 500 | 400 | 320 | 250 | 200 | 8/2 | 5x15.3 |
| GCH 500/1SF | 320 | 250 | 200 | 160 | 125 | 12.5/3 | 5x15.3 |
| GCH 500/1HF | 200 | 160 | 125 | 100 | 80 | 20/5 | 5x15.3 |
| GCH 500/2N | 1000 | 800 | 630 | 500 | 400 | 4 | 5x15.3 |
| GCH 500/2NF | 1000 | 800 | 630 | 500 | 400 | 4/1 | 5x15.3 |
| GCH 500/2SF | 630 | 500 | 400 | 320 | 250 | 6.3/1.5 | 5x15.3 |
| GCH 1000/1N | 1000 | 800 | 630 | 500 | 400 | 8 | 7x22 |
| GCH 1000/1NF | 1000 | 800 | 630 | 500 | 400 | 8/2 | 7x22 |
| GCH 1000/1SF | 800 | 630 | 500 | 400 | 320 | 16/4 | 7x22 |
| GCH 1000/2N | 2000 | 1600 | 1250 | 1000 | 800 | 4 | 7x22 |
| GCH 1000/2NF | 2000 | 1600 | 1250 | 1000 | 800 | 4/1 | 7x22 |
| GCH 1000/2SF | 1600 | 1250 | 1000 | 800 | 650 | 8/2 | 7x22 |
| GCH 1600/1N | 1600 | 1250 | 1000 | 800 | 630 | 8 | 9x27 |
| GCH 1600/1NF | 1600 | 1250 | 1000 | 800 | 630 | 8/2 | 9x27 |
| GCH 1600/1SF | 1000 | 800 | 630 | 500 | 400 | 12.5/3 | 9x27 |
| GCH 1600/2N | 3200 | 2500 | 2000 | 1600 | 1250 | 4 | 9x27 |
| GCH 1600/2NF | 3200 | 2500 | 2000 | 1600 | 1250 | 4/1 | 9x27 |
| GCH 1600/2SF | 2000 | 1600 | 1250 | 1000 | 800 | 6.3/1.5 | 9x27 |
| GCH 2000/1N | 2000 | 1600 | 1250 | 1000 | 800 | 8 | 10x28 |
| GCH 2000/1NF | 2000 | 1600 | 1250 | 1000 | 800 | 8/2 | 10x28 |
| GCH 2000/1SF | 1250 | 1000 | 800 | 630 | 500 | 12.5/3 | 10x28 |
| GCH 2000/2N | 4000 | 3200 | 2500 | 2000 | 1600 | 4 | 10x28 |
| GCH 2000/2NF | 4000 | 3200 | 2500 | 2000 | 1600 | 4/1 | 10x28 |
| GCH 2000/2SF | 2500 | 2000 | 1600 | 1250 | 1000 | 6.3/1.5 | 10x28 |
| GCH 2500/1N | 2500 | 2000 | 1600 | 1250 | 1000 | 6.4 | 10x28 |
| GCH 2500/1NF | 2500 | 2000 | 1600 | 1250 | 1000 | 6.4/1.6 | 10x28 |
| GCH 2500/1SF | 1600 | 1250 | 1000 | 800 | 630 | 10/2.5 | 10x28 |
| GCH 2500/2N | 5000 | 4000 | 3200 | 2500 | 2000 | 3.2 | 10x28 |
| GCH 2500/2NF | 5000 | 4000 | 3200 | 2500 | 2000 | 3.2/0.8 | 10x28 |
| GCH 2500/2SF | 3200 | 2500 | 2000 | 1600 | 1250 | 5/1.25 | 10x28 |

* FEM classification: switches per hour on control pendant

1Bm (M3) = 150 switches per hour, 25% duty

1Am (M4) = 180 switches per hour, 30% duty

2m (M5) = 240 switches per hour, 40% duty

3m (M6) = 300 switches per hour, 50% duty

4m (M7) = 360 switches per hour, 60% duty